

In accordance to Annex III of Regulation (EU) Nr. 305/2011

 Declaration of performance No. **Identification code of the product-type**
LE-H67611-18-10 BUESSCHERPLAN 1800 HP
Purpose

- Roof waterproofing sheet loose laid with ballast and below other utility layers
- Exposed roof waterproofing sheet mechanically fastened

Name, contact producer

BÜSSCHER & HOFFMANN GmbH

4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

 system2+ EN 13956:2012
EN 13956:2012
Harmonized standard EN 13956:2012
Notified body 0679 **CSTB** 84 Avenue Jean Jaurès, Champs-sur-Marne, F-77447 Marne-la-Vallée cedex 2
Certificate of conformity 0679-CPR-1220
Declared performance

Essential characteristics	Performance	Harmonized technical specification
Watertightness (Verf. B)	bestanden	EN 13956:2012 EN 13956:2012
External fire exposure	Broof(t1) ^[1]	EN 13956:2012 EN 13956:2012
Reaction to fire test	E	EN 13956:2012 EN 13956:2012
Peel resistance of joints	≥ 200 N/50mm	EN 13956:2012 EN 13956:2012
Shear resistance of joints long./trans.	≥ 1100 N/50mm	EN 13956:2012 EN 13956:2012
Tensile force long./trans.	≥ 1200/1100 N/50mm	EN 13956:2012 EN 13956:2012
Elongation at single-end breaking force	≥ 15/15 %	EN 13956:2012 EN 13956:2012
Resistance to impact (rigid substrate)	≥ 1000 mm	EN 13956:2012 EN 13956:2012
Resistance to impact (flexible substrate)	≥ 2000 mm	EN 13956:2012 EN 13956:2012
Resistance to static loading	≥ 28 kg	EN 13956:2012 EN 13956:2012
Resistance to tearing (nail shank) long./trans.	≥ 180 N	EN 13956:2012 EN 13956:2012
Foldability	≤ -25 °C	EN 13956:2012 EN 13956:2012
Root resistance	NPD	EN 13956:2012 EN 13956:2012

Essential characteristics

UV-exposure

Performance

Stufe 0

**Harmonized technical
specification**

EN 13956:2012

EN 13956:2012

[1] according to certified system

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



**Bmstr. Dipl. Ing. Karl Landl
General Manager**

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.